

# AURA SoHo™ Accessories



Optional Module Bay



## External Microphones Set of 2 CP-2016-007

Expand the range of your Aura SoHo™ Conference Phone by adding a pair of external microphones for use in larger conference rooms.

- Each package includes 2 microphones that plug right into your unit.
- Perfect for larger conference rooms or large conference tables



## Bluetooth® Module CP-2016-004

The Bluetooth® adapter Module allows you to pair your mobile phone, PDA, or computer to the Aura SoHo™ Conference Phone for professional conferencing. Just plug the module into the Accessory Bay and pair with your Bluetooth® device and you're ready to make conference calls; no software is needed. If you want to make conference calls using your analog phone line later, you can make your calls as usual, without having to remove the module.



## Digital Module CP-2016-003

The Digital adapter Module allows you to use the Aura SoHo™ Conference Phone with your existing PBX phone system. The Digital Module plugs right into the Accessory Bay of the Aura SoHo™ Conference Phone, with no software needed. The Digital Module is compatible with most PBX Systems. You can view the complete list on the Spracht web site, at [www.spracht.com](http://www.spracht.com)

# AURA SoHo™ Accessories



## PRODUCT SPECIFICATIONS

### External Microphones

Part No. CP-2016-007, UPC 800807300217, Master Carton Quantity: 4

Omni-directional microphone	Weight: 2.2 oz (69g)
Frequency response: 100 - 15,000 Hz	Dimensions: 2.8" (72mm)L x 2.5" (63.5mm)W x 1.1" (28mm) H maximum body diameter
Open Circuit Sensitivity: -50 dB (3.1 mV) re 1V at 1 Pa	
Impedance: 600 Ohms	Output Connector: RJ22 mini plug on cable
Maximum Input Sound Level: 119 dB SPL, 1 kHz at 1% T.H.D.	Cable: Permanently attached 2 meter (~ 6') cable with Molded RJ22 mini plug at output end
Dynamic Range (Typical): 82 dB, 1 kHz at 1 Pa	
Signal to Noise Ratio: 57 dB, 1 kHz at 1 Pa	
Power Requirements: 2.5 V DC 500 $\mu$ A power from main unit	

### Bluetooth® Module

Part No. CP-2016-004, UPC 800807300248, Master Carton Quantity: 4

Technology: Bluetooth Class 2, 2.0+EDR	RX Sensitivity: -82 dBm
Chip Set: CSR BlueCore2	Transmission rate: 720 Kbps/2 Mbps/3 Mbps
Frequency: 2.402 GHz to 2.480 GHz	Range: indoors 10 Meter (30 Feet)
Modulation: FHSS/GFSK/DQPSK/DPSK	Power Supply: 5 VDC, 0.12 A max
RF Channel: 79	Dimensions: 1.9" (49mm) x 1.9" (49mm) x 0.76" (19.5mm)
Channel Intervals: 1 MHz	Connector: 50 pin dual row 2mm x 25 pin
TX Power Out: +4 dBm	Indicators: Blue and Amber LED

### Digital Module

Part No. CP-2016-003, UPC 800807300231, Master Carton Quantity: 4

Input Impedance: 120 R 0.15 W
Input Power: 0.25 W max
Output Impedance: 600 ohm
Output Level: AC 0.7 V max
Frequency Response: 200 Hz to 3.5 KHz
Indicators: Hook Off Green LED
Power Supply: 5 V DC, 0.1 A max
Connector: RJ22, 4 of 4 pin from Phone, RJ22 4 of 4 pin for Handset
Dimensions: 1.9" (49mm) x 1.9" (49mm) x 0.76" (19.5mm)